



Rebates up to  
**\$2,400**

## AeroTherm® Series Heat Pump (RE)

### Product Features:

- ENERGY STAR® Qualified
- The AeroTherm® Series Control Panel
- Operating Modes Offer Flexibility
- Quiet Operation
- Can Be Laid Down for Easier Transportation
- Easily Accessible Top Mounted Washable Air Filter
- 2" Non-CFC Foam Insulation
- Water Connections - 3/4" NPT
- Protective Anode Rod
- T&P Relief Valve
- Operating Air Temperature Range of 35-120°F for the Heat Pump
- Vitraglas® tank lining with Microban®

## Heat Pump Water Heater



### AeroTherm® Model

C.E.C. Listed

Model Number	Rated Nominal Volume		DOE Rated Storage Volume	First Hour Rating	Uniform Energy Factor	Recovery at 90°F Rise*				A Floor to Top of Heater in.	B Jacket Dia. in.	C Floor to Water Conn. in.	D C/L of Water Conn. in.	E Floor to T&P Conn. in.	F Floor to Condensate Conn. in.	G Water Conn. Size NPT in.	Approx. Shipping Weight lbs.
	U.S. Gal.	Imp. Gal.				U.S. GPH		Imp. GPH									
	Gal.	Gal.				Compressor Only	Compressor +Element	Compressor Only	Compressor +Element								
★ RE2H50S10	50	42	45	65	3.44	6	24	5	20	59 3/16	21 1/4	60 3/4	8	38 7/8	46 13/16	3/4	195
★ RE2H65T10	65	54	65	79	3.64	6	24	5	20	63 1/4	25	65 1/2	8	42 7/8	51 7/8	3/4	236
★ RE2H80T10	80	67	75	88	3.59	6	24	5	20	70 13/16	25	73 1/2	8	50 3/8	58 11/16	3/4	259
Model Number	Rated Nominal Volume		DOE Rated Storage Volume	First Hour Rating	Uniform Energy Factor	Recovery at 50°C Rise*				A Floor to Top of Heater mm.	B Jacket Dia. mm.	C Floor to Water Conn. mm.	D C/L of Water Conn. mm.	E Floor to T&P Conn. mm.	F Floor to Condensate Conn. mm.	G Water Conn. Size NPT mm.	Approx. Shipping Weight kg.
	Liters/Hour					Liters/Hour											
	Liters	Liters				Compressor Only	Compressor +Element										
★ RE2H50S10	189	170	246	246	3.44	23	91	1503	552	1543	203	987	1189	19	88		
★ RE2H65T10	246	246	299	299	3.64	23	91	1619	635	1664	203	1216	1305	19	107		
★ RE2H80T10	303	284	333	333	3.59	23	91	1799	635	1867	203	1280	1491	19	117		